



RECHARGEABLE VRLA BATTERIES AND BATTERY CHARGERS



46
years
1970-2016

CELEBRATING 46 YEARS OF INNOVATION

Engineered With Vision. Built With Care.

Providing our customers with reliable, yet economical, products is the corner stone of the Power-Sonic mission. The Power-Sonic Corporation has been a leading force since 1970 in the supply of high quality cost effective batteries. Power-Sonic markets an extensive range of rechargeable sealed lead acid batteries worldwide. These batteries envelop a broad spectrum of electronic and industrial applications, either as the prime or standby power source. Engineers and buyers continue to insist on Power-Sonic batteries, wherever reliable and cost effective DC power is required.

Power-Sonic is dedicated to continual product development to improve the performance and reliability of our product range. New batteries are constantly being introduced to meet the ever evolving needs of industry. We strive to produce batteries with superior performance characteristics and value, through advanced engineering and state-of-the art manufacturing processes, coupled with the use of premium raw materials.

We've Got The Power.™



General Purpose Design

* FR: UL94 V-0 flame retardant case & cover

| Model | Nominal Voltage V | Nominal Capacity A.H. | Current @ 20-hr. rate mA | Length | | Width | | Height | | Ht. Over Terminal | | Weight | | Standard Terminals |
|---------------|-------------------|-----------------------|--------------------------|--------|-----|-------|------|--------|------|-------------------|-----|--------|-------|--------------------|
| | | | | in. | mm | in. | mm | in. | mm | in. | mm | lbs. | kgs. | |
| PS-260 | 2 | 6.0 | 300 | 1.97 | 50 | 1.34 | 34 | 3.94 | 100 | 4.13 | 105 | 0.89 | 0.40 | F1 |
| PS-445 | 4 | 4.5 | 225 | 1.89 | 48 | 2.09 | 53 | 3.70 | 94 | 3.86 | 98 | 1.30 | 0.59 | F2 |
| PS-490 | 4 | 9.0 | 450 | 4.01 | 102 | 1.73 | 44 | 3.74 | 95 | 4.02 | 102 | 2.20 | 1.00 | F2 |
| PS-4100 | 4 | 10.0 | 500 | 4.01 | 102 | 1.97 | 50 | 3.70 | 94 | 3.85 | 98 | 2.50 | 1.13 | F1 |
| PS-605 | 6 | 0.5 | 25 | 2.24 | 57 | 0.55 | 14 | 1.97 | 50 | 1.97 | 50 | 0.20 | 0.09 | WL |
| PS-610 | 6 | 1.1 | 55 | 2.00 | 51 | 1.65 | 42 | 2.00 | 51 | 2.20 | 56 | 0.44 | 0.20 | F1 |
| PS-612 | 6 | 1.4 | 70 | 3.82 | 97 | 0.94 | 24 | 2.00 | 51 | 2.20 | 56 | 0.66 | 0.30 | F1 |
| PS-621 | 6 | 2.0 | 100 | 1.69 | 43 | 1.46 | 37 | 2.99 | 76 | 2.99 | 76 | 0.75 | 0.34 | F1 |
| PS-628 | 6 | 2.9 | 145 | 2.60 | 66 | 1.30 | 33 | 3.86 | 98 | 4.06 | 103 | 1.30 | 0.59 | F1 |
| PS-630 | 6 | 3.5 | 175 | 5.28 | 134 | 1.34 | 34 | 2.35 | 60 | 2.56 | 65 | 1.37 | 0.62 | F1 |
| PS-632 | 6 | 3.5 | 175 | 2.60 | 66 | 1.30 | 33 | 4.65 | 118 | 4.80 | 122 | 1.65 | 0.83 | F1 |
| PS-640 | 6 | 4.5 | 225 | 2.76 | 70 | 1.86 | 47 | 3.94 | 100 | 4.25 | 108 | 1.60 | 0.73 | F1 |
| PS-650LS & LF | 6 | 5.0 | 250 | 2.64 | 67 | 2.64 | 67 | 3.94 | 100 | 4.64 | 118 | 1.80 | 0.82 | F1 or SP |
| PS-665 | 6 | 6.5 | 325 | 3.86 | 98 | 2.20 | 56 | 3.78 | 96 | 4.02 | 102 | 2.70 | 1.22 | FP |
| PS-670 | 6 | 7.0 | 350 | 5.95 | 151 | 1.34 | 34 | 3.70 | 94 | 3.94 | 100 | 2.42 | 1.10 | F1 |
| PS-682 | 6 | 9.0 | 450 | 3.86 | 98 | 2.20 | 56 | 4.65 | 118 | 4.72 | 120 | 3.20 | 1.45 | F1 |
| PS-6100 | 6 | 12.0 | 600 | 5.95 | 151 | 2.00 | 51 | 3.70 | 94 | 3.86 | 98 | 4.30 | 1.95 | F1 or F2 |
| PS-6120FP | 6 | 13.0 | 650 | 4.25 | 108 | 2.80 | 71 | 5.55 | 141 | 5.55 | 141 | 4.80 | 2.18 | FP |
| PS-6200 | 6 | 20.0 | 1000 | 6.18 | 157 | 3.27 | 83 | 4.92 | 125 | 4.92 | 125 | 7.10 | 3.22 | NB1 |
| PS-6360 | 6 | 36.0 | 1800 | 6.25 | 159 | 3.35 | 85 | 6.50 | 165 | 6.93 | 176 | 12.10 | 5.49 | F2 or NB1 |
| PS-62000 | 6 | 210.0 | 10500 | 12.05 | 306 | 6.65 | 169 | 8.65 | 220 | 8.96 | 228 | 63.93 | 29.00 | T8 |
| PS-832 | 8 | 3.2 | 160 | 5.29 | 134 | 1.44 | 36.5 | 2.49 | 63 | 2.70 | 69 | 1.58 | 0.72 | F1 |
| PS-1208 | 12 | 0.8 | 40 | 3.78 | 96 | 0.98 | 25 | 2.44 | 62 | n/a | n/a | 0.77 | 0.35 | WL |
| PS-1212 | 12 | 1.4 | 70 | 3.78 | 96 | 1.69 | 43 | 2.04 | 52 | 2.28 | 58 | 1.20 | 0.54 | F1 |
| PS-1220 | 12 | 2.5 | 125 | 7.00 | 178 | 1.38 | 35 | 2.36 | 60 | 2.56 | 65 | 2.10 | 0.95 | F1 |
| PS-1221S | 12 | 2.0 | 100 | 5.91 | 150 | 0.80 | 20 | 3.52 | 89 | n/a | n/a | 1.60 | 0.73 | F1/0 |
| PS-1223 | 12 | 2.3 | 115 | 7.17 | 182 | 0.94 | 24 | 2.40 | 61 | 2.40 | 61 | 1.50 | 0.68 | PC |
| PS-1227 | 12 | 2.9 | 145 | 3.11 | 79 | 2.20 | 56 | 3.90 | 99 | 4.13 | 105 | 2.40 | 1.09 | F1 |
| PS-1228 | 12 | 2.8 | 140 | 5.24 | 133 | 1.30 | 33 | 3.82 | 97 | 4.09 | 104 | 2.60 | 1.18 | F1 |
| PS-1229 | 12 | 2.9 | 145 | 7.00 | 178 | 1.38 | 35 | 2.36 | 60 | 2.60 | 66 | 2.30 | 1.04 | F1 |
| PS-1230 | 12 | 3.4 | 170 | 5.24 | 133 | 2.64 | 67 | 2.36 | 60 | 2.60 | 66 | 2.90 | 1.32 | F1 |
| PS-1238 | 12 | 3.8 | 190 | 7.68 | 195 | 1.85 | 47 | 2.91 | 74 | 2.99 | 76 | 3.50 | 1.59 | F1 |
| PS-1250 | 12 | 5.0 | 250 | 3.54 | 90 | 2.76 | 70 | 3.98 | 101 | 4.21 | 107 | 3.50 | 1.59 | F1 or F2 |
| PS-1270 | 12 | 7.0 | 350 | 5.95 | 151 | 2.56 | 65 | 3.70 | 94 | 3.86 | 98 | 4.80 | 2.18 | F1 or F2 |
| PS-1278HD | 12 | 7.8 | 390 | 5.95 | 151 | 2.56 | 65 | 3.68 | 93.5 | 3.90 | 99 | 5.51 | 2.50 | F2 |
| PS-1280 | 12 | 8.0 | 400 | 5.95 | 151 | 2.56 | 65 | 3.72 | 94.5 | 3.90 | 99 | 5.60 | 2.54 | F1 or F2 |
| PS-1282L | 12 | 9.0 | 450 | 7.72 | 196 | 2.20 | 56 | 4.65 | 118 | 4.65 | 118 | 6.90 | 3.13 | F1 |
| PS-1282S | 12 | 9.0 | 450 | 3.86 | 98 | 4.40 | 112 | 4.65 | 118 | 4.65 | 118 | 6.90 | 3.13 | F1 |
| PS-1290 | 12 | 9.0 | 450 | 5.95 | 151 | 2.56 | 65 | 3.70 | 94 | 3.86 | 98 | 6.00 | 2.72 | F2 or NB1 |
| PS-12100 | 12 | 12.0 | 600 | 5.95 | 151 | 4.00 | 102 | 3.70 | 94 | 3.86 | 98 | 8.14 | 3.69 | F1 or F2 |
| PS-12100H | 12 | 10.5 | 525 | 5.94 | 151 | 2.56 | 65 | 4.40 | 112 | 4.67 | 118 | 7.23 | 3.28 | F2 |
| PS-12120 | 12 | 12.0 | 600 | 5.95 | 151 | 3.86 | 98 | 3.70 | 94 | 3.94 | 100 | 7.92 | 3.59 | F2 or NB1 |
| PS-12120L | 12 | 12.0 | 600 | 8.45 | 215 | 2.75 | 70 | 5.75 | 146 | 5.75 | 146 | 9.50 | 4.32 | FP |
| PS-12140 | 12 | 14.0 | 700 | 5.95 | 151 | 3.86 | 98 | 3.70 | 94 | 3.94 | 100 | 9.00 | 4.09 | F2 |
| PS-12180 | 12 | 18.0 | 900 | 7.13 | 181 | 3.00 | 76 | 6.59 | 167 | 6.59 | 167 | 12.60 | 5.72 | F2, NB2, T12 |
| PS-12180HD-M5 | 12 | 18.0 | 900 | 7.14 | 181 | 3.03 | 77 | 6.59 | 167 | 6.59 | 167 | 13.38 | 6.07 | T12 |
| PS-12200 | 12 | 20.0 | 1000 | 7.13 | 181 | 3.00 | 76 | 6.57 | 167 | 6.50 | 165 | 13.20 | 6.00 | NB1 |
| PS-12260 | 12 | 26.0 | 1300 | 6.56 | 167 | 6.97 | 177 | 4.92 | 125 | 4.92 | 125 | 17.00 | 7.71 | F2, NB2, T12 |
| PS-12280 | 12 | 28.0 | 1400 | 6.50 | 165 | 4.92 | 125 | 6.97 | 177 | 6.97 | 177 | 20.10 | 9.14 | NB1 |
| PS-12330 | 12 | 33.0 | 1650 | 7.72 | 196 | 5.14 | 131 | 6.22 | 158 | 7.00 | 178 | 21.40 | 9.73 | NB3 |
| PS-12350 | 12 | 35.0 | 1750 | 7.72 | 196 | 5.14 | 131 | 6.22 | 158 | 7.00 | 178 | 23.40 | 10.64 | NB3 or T6 |
| PS-12400 | 12 | 40.0 | 2000 | 7.76 | 197 | 6.50 | 165 | 6.69 | 170 | 6.69 | 170 | 29.10 | 13.20 | NB4 |
| PS-12550 | 12 | 55.0 | 2750 | 9.04 | 230 | 5.45 | 138 | 8.15 | 207 | 8.98 | 228 | 36.00 | 16.33 | U or T6 |
| PS-12750 | 12 | 75.0 | 3750 | 10.25 | 260 | 6.60 | 168 | 8.15 | 207 | 8.98 | 228 | 50.60 | 22.95 | U or T6 |
| PS-121000 | 12 | 100.0 | 5000 | 12.00 | 305 | 6.60 | 168 | 8.15 | 207 | 8.98 | 228 | 68.00 | 30.84 | U or T6 |
| PS-121100 | 12 | 110.0 | 5500 | 13.00 | 330 | 6.73 | 171 | 8.35 | 212 | 8.66 | 220 | 69.50 | 31.52 | T11 |
| PS-121400FR* | 12 | 140.0 | 7000 | 13.50 | 343 | 6.73 | 171 | 10.80 | 274 | 11.15 | 283 | 99.00 | 44.91 | T11 |
| PS-122500 | 12 | 260.0 | 13000 | 20.55 | 522 | 10.55 | 268 | 8.66 | 220 | 8.90 | 226 | 161.00 | 73.00 | T11 |

High-Rate Discharge Design / PSH Series

* FR: UL94 V-0 flame retardant case & cover

| Model | Nominal Voltage V | Nominal Capacity A.H. | Current @ 20-hr. rate mA | Length | | Width | | Height | | Ht. Over Terminal | | Weight | | Standard Terminals |
|--------------|-------------------|-----------------------|--------------------------|--------|-----|-------|----|--------|------|-------------------|-----|--------|------|--------------------|
| | | | | in. | mm | in. | mm | in. | mm | in. | mm | lbs. | kgs. | |
| PSH-655FR* | 6 | 5.5 | 275 | 2.76 | 70 | 1.85 | 47 | 3.94 | 100 | 4.17 | 106 | 2.10 | 0.95 | F1 |
| PSH-1255FR* | 12 | 6.0 | 300 | 3.54 | 90 | 2.76 | 70 | 3.98 | 101 | 4.21 | 107 | 4.00 | 1.81 | F2 |
| PSH-1280FR* | 12 | 8.5 | 400 | 5.95 | 151 | 2.56 | 65 | 3.72 | 94.5 | 3.90 | 99 | 5.75 | 2.61 | F2 |
| PSH-12100FR* | 12 | 10.5 | 525 | 5.94 | 151 | 2.56 | 65 | 4.37 | 111 | 4.61 | 117 | 7.00 | 3.18 | F2 |
| PSH-12180FR* | 12 | 21.0 | 1050 | 7.14 | 181 | 3.03 | 77 | 6.59 | 167 | 6.59 | 167 | 13.20 | 5.99 | NB2 |

High-Rate Discharge, Long Life Design / PHR Series

* FR: UL94 V-0 flame retardant case & cover

| Model | Nominal Voltage (V) | Watts per Cell @ 15-min. | Rated Capacity (A.H.) 20-hr. | Length | | Width | | Height | | Ht. Over Terminal | | Weight | | Standard Terminals |
|------------|---------------------|--------------------------|------------------------------|--------|-----|-------|-----|--------|-----|-------------------|-----|--------|------|--------------------|
| | | | | in. | mm | in. | mm | in. | mm | in. | mm | lbs. | kgs. | |
| PHR-12100* | 12 | 93 | 27 | 6.46 | 164 | 4.92 | 125 | 6.89 | 175 | 6.50 | 165 | 20.9 | 9.48 | T12 |
| PHR-12150* | 12 | 150 | 36 | 7.68 | 195 | 5.12 | 130 | 6.46 | 164 | 6.57 | 167 | 22.5 | 10.2 | T6 |
| PHR-12200* | 12 | 225 | 58 | 9.02 | 229 | 5.43 | 138 | 7.87 | 200 | 7.99 | 203 | 38.1 | 17.3 | T6 |
| PHR-12300* | 12 | 324 | 82 | 10.20 | 259 | 6.61 | 168 | 8.19 | 208 | 8.31 | 211 | 52.5 | 23.8 | T6 |
| PHR-12350* | 12 | 370 | 95 | 12.00 | 305 | 6.61 | 168 | 8.15 | 207 | 8.27 | 210 | 60.4 | 27.4 | T6 |
| PHR-12400* | 12 | 430 | 110 | 12.81 | 326 | 6.69 | 170 | 8.39 | 213 | 8.50 | 216 | 69.2 | 31.4 | T8 |
| PHR-12500* | 12 | 492 | 150 | 13.19 | 335 | 6.77 | 172 | 10.83 | 275 | 10.94 | 278 | 92.6 | 42.0 | T8 |
| PHR-12550* | 12 | 539 | 155 | 13.19 | 335 | 6.77 | 172 | 10.83 | 275 | 10.94 | 278 | 93.5 | 42.4 | T8 |

Long Life Design / PG Series

* FR: UL94 V-0 flame retardant case & cover


| Model | Nominal Voltage V | Rated Capacity (A.H.) | | | Length | | Width | | Height | | Ht. Over Terminal | | Weight | | Standard Terminals |
|--------------|-------------------|-----------------------|-------|-------|--------|-----|-------|-----|--------|-----|-------------------|-----|--------|-------|--------------------|
| | | 10-hr. | 5-hr. | 1-hr. | in. | mm | in. | mm | in. | mm | in. | mm | lbs. | kgs. | |
| PG-6V210FR* | 6 | 210.0 | 180.5 | 126.0 | 12.70 | 323 | 7.00 | 178 | 8.98 | 228 | 9.21 | 234 | 71.6 | 32.5 | T11 |
| PG-12V28FR* | 12 | 28.0 | 25.5 | 18.6 | 6.56 | 167 | 6.96 | 177 | 4.92 | 125 | 4.92 | 125 | 18.5 | 8.4 | T12 |
| PG-12V35FR* | 12 | 35.0 | 32.5 | 27.0 | 7.72 | 196 | 5.10 | 130 | 6.22 | 158 | 6.97 | 177 | 24.5 | 11.1 | T6 |
| PG-12V42FR* | 12 | 42.0 | 36.0 | 25.2 | 7.76 | 197 | 6.50 | 165 | 6.69 | 170 | 6.14 | 156 | 32.0 | 14.5 | T6 |
| PG-12V55FR* | 12 | 56.0 | 47.5 | 33.0 | 9.04 | 230 | 5.45 | 138 | 8.15 | 207 | 8.43 | 214 | 36.0 | 16.3 | T6 |
| PG-12V75FR* | 12 | 75.0 | 64.5 | 45.0 | 13.70 | 348 | 6.57 | 167 | 7.00 | 178 | 6.73 | 171 | 54.0 | 24.54 | T6 |
| PG-12V75TFR* | 12 | 75.0 | 64.5 | 45.0 | 10.24 | 260 | 6.61 | 168 | 8.27 | 210 | 8.51 | 216 | 54.0 | 24.54 | T6 |
| PG-12V100FR* | 12 | 100.0 | 87.0 | 60.8 | 12.05 | 306 | 6.61 | 168 | 8.27 | 210 | 8.51 | 216 | 69.5 | 31.5 | T6 |
| PG-12V103FR* | 12 | 103.0 | 88.5 | 61.8 | 13.00 | 330 | 6.80 | 173 | 8.35 | 212 | 8.66 | 220 | 70.0 | 31.8 | T11 |
| PG-12V120FR* | 12 | 124.0 | 106.5 | 74.4 | 16.14 | 410 | 6.97 | 177 | 8.30 | 211 | 8.86 | 225 | 82.0 | 37.2 | T11 |
| PG-12V140FR* | 12 | 144.0 | 120.5 | 84.0 | 13.50 | 343 | 6.73 | 171 | 10.79 | 274 | 11.02 | 280 | 101.0 | 45.9 | T11 |
| PG-12V150FR* | 12 | 153.0 | 131.5 | 91.8 | 19.10 | 485 | 6.70 | 170 | 9.53 | 242 | 8.82 | 224 | 103.0 | 46.7 | T11 |
| PG-12V200FR* | 12 | 210.0 | 180.5 | 126.0 | 20.55 | 522 | 9.45 | 240 | 8.58 | 218 | 8.82 | 224 | 141.0 | 64.1 | T11 |

Terminal Options

F1  **FASTON**
0.187" x 0.032"
quick disconnect tabs.

F2  **FASTON**
0.250" x 0.032"
quick disconnect tabs

FP  **FASTON POLARIZED**
Positive: "F2", Negative: "F1"

F1/O 
4.8
0.6
21


SP  **SPRING TERMINALS**
Fully collapsible positive and negative contacts


WL **INSULATED WIRE LEADS**
• Molex Housing 5264-02 & 5263-PBT plug on PS-605
• AMP Housing 1-480318-0 & 8116-1 on PS-1208


PC **PRESSURE CONTACTS**


TH  **TOY BATTERY CONNECTORS**
H-connector PS-6120 TH


TS  **TOY BATTERY CONNECTORS**
S-connector PS-6120 TS

U 
Positive
Negative
Torque: 11.0~14.7 Nxm

NB1 
Torque: 2.0~3.0 Nxm

NB2 
Torque: 3.9~5.4 Nxm

NB3 
Torque: 3.9~5.4 Nxm

NB4 
Torque: 3.9~5.4 Nxm

B, T6 **THREADED INSERT - 6mm STUD**
Torque: 3.9~5.4 Nxm

T8 **THREADED INSERT - 6mm STUD**
Torque: 3.9~5.4 Nxm

T11 **THREADED INSERT - 8mm STUD**
Torque: 11.0~14.7 Nxm

T12 **THREADED INSERT - 5mm STUD**
Torque: 2.0~3.0 Nxm

SLA CHARGERS: Automatic Switch-Mode and Float Chargers



"A-C" Series:

Automatic chargers are "switching" type devices which operate without the use of transformers. I.C.'s control and regulate current and voltage and automatically switch from the higher fast charge voltage to the lower float voltage when batteries are very close to being fully charged. At the float voltage it is safe to leave the battery connected to the charger indefinitely, making charging pretty much fool-proof. This type of charger is ideal for cyclic applications where recharge time is critical and timely charge termination cannot be counted on. This type of charger ensures optimum battery performance & service life.

"F-C" Series:

Float chargers are designed to provide optimum life for batteries used in standby applications where charging is continuous. The chargers deliver a constant voltage of 2.25 to 2.30 volts per cell which allow the battery to seek its own current level and maintain itself in a fully charged condition. This series is best suited for burglar and fire alarm equipment, emergency lighting, memory protection, or UPS systems where the battery serves as back-up power to the AC source.

| Model | Nominal Voltage | Output Voltage Float/Fast Charge | Output Current mA | Type Automatic | Dimensions: in. (mm) | | | Weight | | Charger Design |
|------------------|-----------------|----------------------------------|-------------------|----------------|----------------------|------------|-----------|--------|------|----------------|
| | | | | | Length | Width | Height | lbs. | kgs. | |
| PSC-6300A-C* | 6 | 6.75 / 7.35 | 300 | Dual Rate | 2.05 (52) | 1.57 (40) | 2.64 (67) | 0.21 | 0.10 | Plug-in |
| PSC-6300F-C* | 6 | 5.0 / 6.95 | 300 | Float | 2.05 (52) | 1.57 (40) | 2.64 (67) | 0.21 | 0.10 | Plug-in |
| PSC-6500A-C* | 6 | 6.75 / 7.35 | 500 | Dual Rate | 2.05 (52) | 1.57 (40) | 2.64 (67) | 0.21 | 0.10 | Plug-in |
| PSC-6500F-C* | 6 | 5.0 / 6.95 | 500 | Float | 2.05 (52) | 1.57 (40) | 2.64 (67) | 0.21 | 0.10 | Plug-in |
| PSC-61000A-C* | 6 | 6.75 / 7.35 | 1000 | Dual Rate | 2.24 (57) | 1.73 (44) | 3.23 (82) | 0.30 | 0.14 | Plug-in |
| PSC-64000A-C | 6 | 6.75 / 7.35 | 4000 | Dual Rate | 5.43 (138) | 2.83 (72) | 1.65 (42) | 0.90 | 0.41 | Desk Top |
| PSC-12300A-C* | 12 | 13.50 / 14.70 | 300 | Dual Rate | 2.05 (52) | 1.57 (40) | 2.64 (67) | 0.21 | 0.10 | Plug-in |
| PSC-12300F-C* | 12 | 10.0 / 13.8 | 300 | Float | 2.05 (52) | 1.57 (40) | 2.64 (67) | 0.21 | 0.10 | Plug-in |
| PSC-12500A-C* | 12 | 13.50 / 14.70 | 500 | Dual Rate | 2.24 (57) | 1.73 (44) | 3.23 (82) | 0.30 | 0.14 | Plug-in |
| PSC-12500F-C* | 12 | 10.0 / 13.8 | 500 | Float | 2.05 (52) | 1.57 (40) | 2.64 (67) | 0.21 | 0.10 | Plug-in |
| PSC-12800A-C* | 12 | 13.50 / 14.70 | 800 | Dual Rate | 2.24 (57) | 1.73 (44) | 3.23 (82) | 0.30 | 0.14 | Plug-in |
| PSC-122000A-C | 12 | 13.50 / 14.70 | 1800 | Dual Rate | 5.43 (138) | 2.83 (72) | 1.65 (42) | 0.90 | 0.41 | Desk Top |
| PSC-124000A-C | 12 | 13.50 / 14.70 | 4000 | Dual Rate | 5.43 (138) | 2.83 (72) | 1.65 (42) | 0.90 | 0.41 | Desk Top |
| PSC-1210000A-C** | 12 | 13.50 / 14.70 | 10000 | Dual Rate | 8.80 (224) | 5.17 (131) | 3.33 (85) | 4.30 | 1.95 | Desk Top |
| PSC-241000A-C | 24 | 27.00 / 29.40 | 1000 | Dual Rate | 5.43 (138) | 2.83 (72) | 1.65 (42) | 0.90 | 0.41 | Desk Top |

* Note: All plug-in design have 39" (1m) leads. All desktop design have 59" (1.5m) input leads and 39" (1m) output leads. Connectors to the battery are alligator clips with insulated sleeves.

** Note: PSC-1210000A-C is only available for use with input voltages of 90-132V 60 Hz. This charger is ideally suited for batteries from 40-100AH. The charger may also be used for charging batteries from 100-140AH, but the charging time will be increased.

Power-Sonic does not offer chargers for batteries with capacities higher than 100 AH. If you have any queries or difficulties locating a suitable charger for batteries above 100 AH, our Technical Department will be happy to assist you.

All data subject to change without notice.

Further Information

Please refer to our website www.power-sonic.com for a complete range of useful downloads, such as product catalogs, specification sheets, technical manual, material safety data sheets (MSDS), ISO certification, etc.

Contact Information

DOMESTIC SALES
Tel: +1-619-661-2020
Fax: +1-619-661-3650
national-sales@power-sonic.com

CUSTOMER SERVICE
Tel: +1-619-661-2030
Fax: +1-619-661-3648
customer-service@power-sonic.com

TECHNICAL SUPPORT
Tel: +1-619-661-2020
Fax: +1-619-661-3648
support@power-sonic.com

INTERNATIONAL SALES
Tel: +1-650-364-5001
Fax: +1-650-366-3662
international-sales@power-sonic.com